

Specification

□ Frame

Selected edge grain Douglas Fir, 2 piece main frame, decorative profile, 4 3/8" (111 mm). Interior jambliner is factory applied for 6 9/16" (167 mm) jamb or any non standard jamb widths up to 12" (254 mm). Preservative treated after milling. Decorative frame has a consistent appearance to our casement, awning, and specialty windows. 2 piece main frame is glued, screwed and stapled from the back side, leaving the interior free from any nail holes. Frame is joined at the corners with a lap joint, and all 4 corners are glued, screwed, and stapled to provide superior stability and strength.

□ Sash

Edge grain Douglas Fir slimline 2 1/4" (57 mm) X 1 3/4" (44 mm) sash. Joined with a double mortise and tenon for superior strength and stability. Glued and stapled at each corner. Preservative treated after milling.

□ Brickmould

Edge grain Douglas Fir brickmould, 1 3/4" (45 mm) X 1 1/4" (32 mm), stapled and sealed to frame. Screw holds mitred corners tightly together, Sill nosing is screwed from underneath on the exterior, and sealed to frame.

□ Glazing

Edge grain Douglas Fir exterior glazing stop with a specially formulated silicone, exterior and interior, to provide an exceptional watertight seal with minimal sightline appearance, requiring very little long term maintenance.

□ Glass

Dualpane IGU with 1/2" (12 mm) airspace, featuring champagne spacer bar. Options include PPG or Cardinal Low'e coatings, Krypton and/or Argon Gas, as well as various warm edge spacers. An extensive range of Heat Mirror glass representing the highest performing IGU options available.

□ Mullions

Combination units are factory mullied using a combination of sealants and fasteners. Face of exterior mull and head mull is caulked to prevent water and/or air infiltration. Profiled interior mullion covers are factory applied.

□ Prefinish

Stain - Available in an unlimited variety of colors.

- Available in solid, semi transparent, and transparent stain
- Available in different finishes on the exterior and interior (split finish)


Paint - Available in Latex or oil finish

- Available in an unlimited variety of colors.
- Available in different finishes on the exterior and interior (split finish)

All finishes require a final application coat to be applied on site by the general contractor or homeowner after installation of product to ensure that installation nail holes and/or any minor scratches received on site are covered. Final coat must be applied for prefinish to preform as specified.

□ Weatherstripping

Dual weatherstripped with a double finseal mohair at meetrail and lozerone bubble at sides of sash combined with finseal mohair at head and jamb.



Hardware & Screen

- Invisible Balance concealed in the sash.
- Gold tone camlocks lock sash tightly in place.
- Screen is exterior mounted, gold tone aluminum frame with black fibreglass screen cloth.
- Sash do not tilt in.
- Top sash can be fixed in place for single hung window.

Options

- 3" (76 mm) Profiled Brickmould
- 4" (102 mm) Profiled Brickmould
- 5" (127 mm) Profiled Brickmould
- 6" (152 mm) Profiled Brickmould

■ Grids

- ☒ Rectangular ☒ Heritage ☒ Custom
- removable wood grids
- removable stained grids
- removable painted grids
- internal (IGU) grids

SDL(simulated divided lite)

available in 7/8" 1 1/4" & 1 1/2"
optional spacer grid available

TDL(true divided lite)

available 1 1/2" & 2" widths

■ Packed Mullions

available from 1" packed mullion
to 6" packed mullion available
in 1/2" increments.